# TI-500E



The TI-500E is an NTEP approved digital indicator housed in a durable black ABS enclosure. It is equipped with a large easy to read 0.6" LED display. Capable of powering up to  $4-350\Omega$  load cells, this simple device can handle a multitude of functions. A full duplex RS-232 port can transmit data on demand or continuously to match the input requirements of a wide variety of peripheral devices including printers, remote displays and computers. The setup and calibration parameters are shared with other TI series indicators for consistently easy and trouble free use and maintenance. The TI-500E is the leader in reliable performance and value.



# TI-500E

### ENIGMA DIGITAL INDICATOR

# **STANDARD FEATURES & BENEFITS**

- High Quality / Low Cost
- ▶ NTEP Approved for 5,000 Divisions

- Displays up to 50,000 graduations
- $\triangleright$  Drives up to four 350 $\Omega$  Load Cells
- > Stainless Steel Swivel Stand
- Operates on AC Adapter or 12 Volt DC

## **Specifications:**

Load Cell Excitation: +10 VDC

**Load Cell Current:** Drives up to four  $350\Omega$  Load Cells Analog Signal Input Range: 0.2 mV/V min to 3.0 mV/V max **Analog Sensitivity:** 

0.4 μV/grad, minimum

1.0 µV/grad recommended minimum for Legal-for-Trade

A/D Conversion Rate: Up to 25 meas/sec A/D Resolution: Up to 260,000 Internal Counts

Display: 0.6", 6 Digit LED Display

Display Resolution: Up to 50,000 External Grads, Selectable

Key Functions: Units, Zero, Net/Gross, Tare, Print

Annunciators: Gross, Net, kg, lb, Center of Zero, Stable, Tare,

Negative, PCS

Serial Port: Full Duplex RS-232 Format

Power Requirement: 12 VDC, 500 mA Wall Adapter, Included **DC Power Consumption:** 200 mA + 30 mA/350 $\Omega$  Load Cell Operating Temperature: 14°F to 104°F (-10°C to 40°C)

**Indicator Dimensions:** 3.2" x 6.8" x 2.3"


Warrantv: 1 Year Warrantv

**NIST Classification:** 

H-44 Class III at 5,000 Divisions

C.O.C.#94-080A2

#### PHYSICAL DIMENSIONS



#### YOUR AUTHORIZED TRANSCELL DEALER IS:



975 Deerfield Pkwy, Buffalo Grove, IL 60089 Tel (847) 419-9180 Fax (847) 419-1515

(800) 503-9180

www.transcell.net