SP SERIES



The SP Series Digital Bench Scale is an NTEP approved legal for trade, compact, 60 lb or 100 lb capacity scale with remote LED display attached with six feet of cable. An optional 12", 18", or 30" stainless steel column and mounting bracket is available. The scale features a removable stainless steel platform and adjustable feet for leveling.

The SP Series uses full duplex RS-232 serial format to interface with personal computers or remote displays. The unit can transmit on demand or continuously in several popular UPS manifest data protocols.



SP SERIES

STANDARD FEATURES & BENEFITS

APPLICATIONS

- UPS Online System
- Shipping / Receiving
- ▷ Mailroom Use
- Manifest Systems
- Portion Control
- General Purpose Weighing


FEATURES

- ➢ High Quality / Low Cost
- ▷ Large (10" x 13") Platter
- ▷ Full Duplex RS-232 Serial Port
- Two Weighing Units
- ▷ 7 Digit, .5" VFD Display
- ▷ Adjustable feet for leveling
- ▷ Full Digital Calibration

Options

12" stainless steel column and indicator bracket 18" stainless steel column and indicator bracket 30" stainless steel column and indicator bracket

SPECIFICAT	IONS
CONSTRUCTION:	
Indicator Housing:	ABS
Sub-Platform:	ABS & Metal
Platter:	Stainless Steel
Feet:	Non-skid Hard Rubber
DISPLAY:	7-Digit Vacuum Fourescent Display
KEYPAD:	5-Key Tactile Keypad
OVER CAPACITY ANNUNCIATION:	103% of Full Scale Capacity
SERIAL PORT:	Full Duplex, RS-232
	Female DSUB9
OPERATING TEMP RANGE:	32°F to 100°F
	0°C to 40°C
MAIN POWER SOURCE:	AC Adapter, 12VDC, 500 mA, included
WEIGHT:	•
Net Weight:	19.4 lb
Shipping Weight:	21.6 lb
OPTION:	NMC-1 Null Modem Cable



MODEL	CAPACITY
SP-60	60 lb x 0.02 lb (30kg x 0.01 kg)
SP-100	100 lb x 0.05 lb (50 x 0.02 kg)



975 Deerfield Pkwy, Buffalo Grove, IL 60089 Tel (847) 419-9180 Fax (847) 419-1515

(800) 503-9180

www.transcell.net

Specifications and features subject to change without notice.

YOUR AUTHORIZED TRANSCELL DEALER IS: